



Style 1394

Product Data Sheet January 2014

A woven fabric, produced from polypropylene slit-film tapes, which will meet or exceed the following specifications.

Property	Test Method	English Units		SI Units			
		Typical Value		Typical Value			
Mass per Unit Area	ASTM D-5261	4.8	oz/yd ²	163		g/m ²	
Grab Tensile Strength	ASTM D-4632	225	175	lbs	1001	779	N
Grab Tensile Elongation	ASTM D-4632	23	17	%	20	17	%
Mullen Burst	ASTM D-3786	400		lb/in ²	2758		kPa



Produced in Belton, South Carolina, U.S.A.

The foregoing is believed to be an accurate representation of information compiled from inside and/or outside sources, however, because test values, statistical data, and other information presented may be based solely on results of unverified tests made on random samples, information presented may relate only to tested samples and because the conditions in which such information may be used are beyond the control of Belton Industries, Inc., Belton does not guarantee either the accuracy or reliability of the information or the suggestions and recommendations contained herein. Belton assumes no responsibility for the use of information presented herein and hereby disclaims all liabilities which may arise in connection with the use of information herein presented. All specifications, properties, values, statistical data and applications listed herein are provided as information only, without charge or obligation to the recipient or user, and in no way either makes or creates any warranty with respect to any product or modifies, amends or enlarges any warranty made with respect to any product. Final determination of the suitability, reliability and accuracy of the information and suggested uses is solely the responsibility of the user.